

DESOPON[®] DPF

Major component

- Polymer of modified natural/synthetic oil and acrylic acid

Property

- Give full, soft leather with light handle.
- Good filling effect, improve loose grain of belly and flank, reduce part difference.
- Improve dispersion and penetration of acrylic retanning agents and fatliquors.
- Give uniform break and good mill resistance.

Specification

Appearance(25°C):	Liquid or paste
Color:	Yellowish-brown
pH(10% aqueous solution, 25°C):	7.5±1.0
Active matter%:	40.0±2.0
Short chain chlorinated paraffin:	Comply with EU REACH laws and regulations
APEO:	Comply with EU REACH laws and regulations

Application

- Recommended dosage for main fatliquoring:4.0%~10.0% (in terms of shaved wet-blue) . Also can be used in retanning process, recommended dosage:2.0%~4.0%.

Safety

- This is not a hazardous chemical.
- Observe all the precautions required for handling chemicals.
- Read attentively and observe all the recommendations in our **Material Safety Data Sheet**.

DESOPON[®] DPF

Transportation and Storage

- The product has a shelf life of at least one year if it is stored in its tightly sealed original packaging at temperatures between 5°C and 35°C.
- This product should be stored in a cool and dry place, lidded and keep upright. Avoid direct exposure to the sun or frost.
- Appearance may change during storage,if lamination occur, stir well before use properties will not be affected.
- Re-seal the package immediately after using, use up as soon as possible once the package is opened.
- Read attentively and observe all the recommendations in our **Material Safety Data Sheet**.