

DESOADDI® AS5336

Major component

- Matting agent and Polymer.

Property

- Excellent cover properties for scars and grain defects.
- Excellent buffering properties.
- Excellent milling performance.
- Slow drying speed.

Specification

Appearance(25°C):	White pastes
Solid content (%):	~33.0
pH(10.0% aqueous solution, 25°C):	~7.5
Ionicity:	Anionic

Application

- Apply it on the damage region by scraper and some more can be used according to the use condition.
- 5% pigment can be added when it was applied on dyed leathers.
- The leather should be hung up for about 4 hours after being dealt with this product. And polishing it with 400# sandpaper will be better.

Safety

- This is not a hazardous chemical.
- Observe all the precautions required for handling chemicals.
- Read attentively and observe all the recommendations in our **Material Safety Data Sheet**.

DESOADDI® AS5336

Transportation and Storage

- The product has a shelf life of at least one year if it is stored in its tightly sealed original packaging at temperatures between 5°C and 35°C.
- The product should be stored in a cool and dry place, with no throwing, avoid direct exposure to the sun or rain or humidity.
- This product may be stratified during storage, and the application effect will not be affected if using it after mixing evenly.
- Re-seal the package immediately after using, use up as soon as possible once the package is opened.
- Read attentively and observe all the recommendations in our **Material Safety Data Sheet**.