

# DESOCOR<sup>®</sup> CF6320

## Major component

- Mixture of nature oil and synthetic oil.

## Property

- Improve the softness of leather.
- Improve the handle of the leather, from dry and rough to moist and silky handle.
- Improve the color saturation of leather, especially for black color.
- Lubricate the fiber to avoid crack of leather.

## Specification

Appearance(25°C):	Yellowish-brown to brown Viscous liquid
Solid content (%):	~45.0
pH(10.0% aqueous solution, 25°C):	~6.5
Ionicity:	Nonionic

## Application

- Full-grain / corrected-grain leather, on flesh side:

<b>DESOCOR CF6320</b>	300
DESOCOR CP-XY	50
WATER	650

Spray 1 time, according to the condition of the leather, 10-15g/SF, stay overnight

- Full-grain leather, on grain side:

<b>DESOCOR CF6320</b>	100-300
DESOCOR CP-XY	100
LIQUID-DYE	0-50
WATER	650

- Spray 1 or 2 times.

# DESOCOR<sup>®</sup> CF6320

- Nubuck/split suede:

**DESOCOR CF6320** 100-300

DESOCOR CP-XY 100

LIQUID-DYE 0-50

WATER 800

Spray 1-2 times.

## Safety

- This is not a hazardous chemical.
- Observe all the precautions required for handling chemicals.
- Read attentively and observe all the recommendations in our **Material Safety Data Sheet**.

## Transportation and Storage

- The product has a shelf life of at least one year if it is stored in its tightly sealed original packaging at temperatures between 5°C and 35°C.
- The product should be stored in a cool and dry place, with no throwing, avoid direct exposure to the sun or rain or humidity.
- This product may be stratified during storage, and the application effect will not be affected if using it after mixing evenly.
- Re-seal the package immediately after using, use up as soon as possible once the package is opened.
- Read attentively and observe all the recommendations in our **Material Safety Data Sheet**.