

# DESOTOP<sup>®</sup> TU4235

## Major component

- matting agent modified polyurethane emulsion.

## Property

- Used for water-based finishing top coat to generate good matting effect.
- Endow the leather with excellent physical properties.
- Bring a pleasant delicate silky feeling.

## Specification

Appearance(25°C):	White liquid
Solid Content(%):	~19.0
pH(10.0% aqueous solution, 25°C):	~8.0
Ionicity:	Anionic

## Application

- **DESOTOP TU4235** is usually used in spraying operations.
- **DESOTOP TU4235** can be combined with other water-based polyurethane top coatings (such as DESOTOP TU4250-N) to adjust the gloss of the product.
- **DESOTOP TU4235** can be used together with other additives such as hand-feeling agent, hand-feeling wax to improve the leather's hand feeling.
- Cross-linking agent can be used to improve the physical properties of the finished leather.
- Before use, DESOTOP TU4250-N, hand-feeling agent, and cross-linking agent must be properly matched according to the target requirements, and spraying experiments should be carried out to confirm the gloss and physical properties.

# DESOTOP<sup>®</sup> TU4235

## Safety

- This is not a hazardous chemical.
- Observe all the precautions required for handling chemicals.
- Read attentively and observe all the recommendations in our **Material Safety Data Sheet**.

## Transportation and Storage

- The product has a shelf life of at least one year if it is stored in its tightly sealed original packaging at temperatures between 5°C and 35°C.
- The product should be stored in a cool and dry place, with no throwing, avoid direct exposure to the sun or rain or humidity.
- This product may be stratified during storage, and the application effect will not be affected if using it after mixing evenly.
- Re-seal the package immediately after using, use up as soon as possible once the package is opened.
- Read attentively and observe all the recommendations in our **Material Safety Data Sheet**.